

LIS009492167B2

(12) United States Patent

Shelton, IV et al.

(10) Patent No.: US 9,492,167 B2

(45) **Date of Patent:** Nov. 15, 2016

(54) ARTICULATABLE SURGICAL DEVICE WITH ROTARY DRIVEN CUTTING MEMBER

(71) Applicant: Ethicon Endo-Surgery, Inc.,

Cincinnati, OH (US)

(72) Inventors: Frederick E. Shelton, IV, Hillsboro,

OH (US); Mark S. Ortiz, Milford, OH

(US)

(73) Assignee: Ethicon Endo-Surgery, LLC,

Guaynabo, PR (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 757 days.

(21) Appl. No.: 13/803,862

(22) Filed: Mar. 14, 2013

(65) Prior Publication Data

US 2013/0197556 A1 Aug. 1, 2013

Related U.S. Application Data

- (63) Continuation of application No. 11/277,324, filed on Mar. 23, 2006, now abandoned.
- (51) **Int. Cl.**A61B 17/068 (2006.01)

 A61B 1/005 (2006.01)

 (Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

66,052 A 6/1867 Smith 662,587 A 11/1900 Blake (Continued)

FOREIGN PATENT DOCUMENTS

AU 2008207624 A1 3/2009 AU 2010214687 A1 9/2010 (Continued)

OTHER PUBLICATIONS

European Examination Report, Application No. 07251221.3, dated Dec. 10, 2009 (5 pages).

(Continued)

Primary Examiner - Gloria R Weeks

(57) ABSTRACT

Methods and devices are provided for controlling movement of a working end of a surgical device. In one embodiment, methods and devices are provided for moving an end effector on a distal end of a surgical fastening device. Movement can include rotational movement of the end effector about an axis of the shaft, articulation of the end effector relative to the shaft, and actuation of an end effector, e.g., closing, firing, and/or cutting. In other embodiments, a single cable actuator is provided and is movable between a first position, in which it is effective to rotate an end effector without actuating (i.e., closing and firing) the end effector, and a second position, in which it is effective to actuate the end effector without rotating the end effector. In other aspects, methods and devices are provided for moving a flexible neck formed on a distal end of an accessory channel for use with an endoscope. Movement of the flexible neck can be used to control positioning of a tool extending through the flexible neck.

20 Claims, 27 Drawing Sheets

